HellermannTyton

TAG73T1-DTH	
	Article Number: 596-00038
	Thermal Transfer Label, 2.0" X 1.0", 1 Across, DTH, White, 3000/RL
HellermannTyton	Rohs
Download drawing Downlo	ad spec sheet
Base Data	
Local Order Numbe	r TAG73T1-DTH
Тур	e TAG73T1
Colo	or White (WH)
Features and Benefit	
	 Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating th need to be dedicated to one printer model.
	• The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.
Product Descriptio	n Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and
	abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The produc
	is supplied on rolls on a 3" cardboard core.
Short Descriptio	n Thermal Transfer Label, 2.0" X 1.0", 1 Across, DTH, White, 3000/RL
Product Dimensions	
Width W (Imperia	I) 2.0 "
Width W (Metric	s) 50.8 mm
Height H (Imperia	I) 1.0 "
Height H (Metric	c) 25.4 mm
Horizontal Repeat HR (metric	:) 25.4 mm
Horizontal Repeat HR (imperia	I) 1.0 "
Print Metho	d Thermal Transfer
Vertical Repeat VR (imperia	I) 1.125 "
Vertical Repeat VR (metric	:) 28.57 mm
Width of Liner WL (imperia	•
Width of Liner WL (metric	e) 55.83 mm
Logistics and Packaging	
Quantity Pe	r reel

Quality Fer	TEEL
Package Quantity	3000
Package Quantity (Metric)	3000
Labels per Row	1

Material and Specifications

Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +140°F (-40°C to +60°C)
Operating Temperature	-40°F to +140°F (-40°C to +60°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized

© HellermannTyton 2015