## HellermannTyton

TAG78T1-795	
Ar	ticle Number: 596-78795
Th	nermal Transfer Label, 3.0" X 4.0", 1 Across, Polyester, Silver , 500/RL
	RoHS
HellermannTyton ¥	KONG .
Download drawing	I spec sheet
Base Data	
Local Order Number	TAG78T1-795
Туре	TAG78T1
Color	Silver (SR)
Features and Benefits	<ul> <li>Thermal transfer labels are made with high performance materials for long term industrial applications.</li> <li>Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.</li> <li>The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.</li> </ul>
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, 3.0" X 4.0", 1 Across, Polyester, Silver , 500/RL
Product Dimensions	
Width W (Imperial)	3.0 "
Width W (Metric)	76.2 mm
Height H (Imperial)	4.0 "
Height H (Metric)	101.6 mm
Horizontal Repeat HR (metric)	
Horizontal Repeat HR (imperial)	
Print Method	Thermal Transfer
Vertical Repeat VR (metric)	104.7 mm
Vertical Repeat VR (imperial)	
Width of Liner WL (metric)	
Width of Liner WL (imperial)	3.12 "
Logistics and Packaging	
Quantity Per	reel
	500

Package Quantity	500
Package Quantity (Metric)	500
Labels per Row	1

## Material and Specifications

Adhesive	Acrylic
Adhesive Shortcut	Acrylic
Adhesive Operating Temperature	-40°F to +300°F (-40°C to +149°C)
Operating Temperature	-40°F to +300°F (-40°C to +149°C)
<b>ROHS</b> Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015