HellermannTyton

TAG83T1-822	
Th	ticle Number: 596-00023 nermal Transfer Label, 4.0" X .312", 1 Across, Polyester, White, 5000/RL
Download drawing	I spec sheet
Base Data Local Order Number	TA C02T4 022
	TAG83T1
	White (WH)
Features and Benefits	
Product Description	Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.
Short Description	Thermal Transfer Label, 4.0" X.312", 1 Across, Polyester, White, 5000/RL
Product Dimensions	
Length L (Imperial)	0.312 "
Length L (Metric)	
Width W (Imperial)	
Width W (Metric)	101.6 mm
Height H (Imperial)	7.87 "
Height H (Metric)	7.52 mm
Horizontal Repeat HR (imperial)	4.0 "
Horizontal Repeat HR (metric)	101.6 mm
Print Method	Thermal Transfer
Vertical Repeat VR (imperial)	0.44 "
Vertical Repeat VR (metric)	11.13 mm

Width of Liner WL (imperial) 4.10 " Width of Liner WL (metric) 104.14 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	5000
Package Quantity (Metric)	5000
Labels per Row	1

Material	Type 822, Polyester, white (WH)
Material Shortcut	822
Adhesive	Acrylic
Adhesive Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US and Canada)	Yes

© HellermannTyton 2015