

TAG96T1-336

Article Number: 596-00026

Thermal Transfer Label, 1.875" X .25", 1 Across, Polyester, White, 5000/RL



Download drawing



Download spec sheet

Base Data

Local Order Number TAG96T1-336

Type TAG96T1

Color White (WH)

- Features and Benefits**
- Thermal transfer labels are made with high performance materials for long term industrial applications.
 - Labels can be printed in any standard thermal transfer printer giving the user options for printing and eliminating the need to be dedicated to one printer model.
 - The labels are available in a wide variety of sizes so that finding a label for a particular application is easy.

Product Description Labels are made with various high performance materials including polyester, metalized polyester, clear polyester, cloth, polyimide and the Durattach label stock. The construction includes an aggressive acrylic adhesive and abrasion and chemical resistant top coatings that are made to accept ink from a thermal transfer printer. The product is supplied on rolls on a 3" cardboard core.

Short Description Thermal Transfer Label, 1.875" X .25", 1 Across, Polyester, White, 5000/RL

Product Dimensions

Length L (Imperial) 0.25 "

Length L (Metric) 6.35 mm

Width W (Imperial) 1.875 "

Width W (Metric) 47.6 mm

Height H (Imperial) 0.25 "

Height H (Metric) 6.35 mm

Horizontal Repeat HR (metric) 47.6 mm

Horizontal Repeat HR (imperial) 1.875 "

Print Method Thermal Transfer

Vertical Repeat VR (imperial) 0.375 "

Vertical Repeat VR (metric) 9.35 mm

Width of Liner WL (metric) 50.8 mm

Width of Liner WL (imperial) 2.0 "

Logistics and Packaging

Quantity Per reel

Package Quantity 5000

Package Quantity (Metric) 5000

Labels per Row 1

Material and Specifications

Material Type 336, Polyester
Material Shortcut 336
Adhesive Shortcut Acrylic
Adhesive Acrylic
Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)
Operating Temperature -40°F to +302°F (-40°C to +150°C)
ROHS Compliant Yes
Certification/Specification UL-Recognized