

TYHCC

Article Number: 598-00199

Handi-Card, .25" X 1.5", Solid Letter C, 36 Per Card, White, 25/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number TYHCC

Type TYHCC

Color White (WH)

- Features and Benefits**
- Handi Cards have a split backing so that a portion of the liner can be removed to expose the markers for easy dispensing.
 - Handi-Cards are kitted on the card so that specific markers can be removed without affecting the other markers on the card.
 - Markers are pre-printed so no additional post printing is required, saving time and money.
 - Label material is a conformable cloth that ensures markers stay on wires and cables for the life of the application.

Product Description HellermannTyton Handi-Cards are easy release pre-printed cloth markers, on a plastic card, with a strong adhesive for a long lasting bond on wire and cable. The markers are available in Solid format where each marker on the card contains the same legend and Sequence format where each marker on the card contains a different number or letter which is usually printed in sequence from lowest to highest in sort order.

Short Description Handi-Card, .25" X 1.5", Solid Letter C, 36 Per Card, White, 25/pkg

Product Dimensions

Length L (Imperial) 1.5 "

Length L (Metric) 38.1 mm

Width W (Imperial) 0.25 "

Width W (Metric) 6.35 mm

Height H (Imperial) 1.5 "

Height H (Metric) 38.1 mm

Bundle Diameter Min. (Imperial) 0.13 "

Bundle Diameter Min. (Metric) 3.40 mm

Bundle Diameter Max. (Imperial) 0.29 "

Bundle Diameter Max. (Metric) 7.50 mm

Outside Diameter Min. (Imperial) 0.13 "

Outside Diameter Min. (Metric) 3.40 mm

Outside Diameter Max. (Imperial) 0.29 "

Outside Diameter Max. (Metric) 7.50 mm

Logistics and Packaging

Quantity Per pack

Package Quantity 25

Package Quantity (Metric) 25

Labels per Column 1

Labels per Row 36

Labels per Sheet 36

Material and Specifications

Material Vinyl Cloth (TYHC)

Material Shortcut TYHC

Adhesive Shortcut Synthetic rubber

Adhesive Rubber

Adhesive Operating Temperature -40°F to +248°F (-40°C to +120°C)

Operating Temperature -40°F to +248°F (-40°C to +120°C)

ROHS Compliant Yes