HellermannTyton

| WC9-6 | |
|----------------------------------|--|
| A | rticle Number: 560-10432 |
| c | lip-Tag marked 6, .128"177", Nylon, White, 300/Pkg |
| | RoHS |
| HellermannTyton | KUT3 |
| | |
| | |
| Download drawing | d spec sheet |
| | |
| Base Data | |
| Local Order Number | |
| | WC9 |
| | r White (WH) |
| Features and Benefits | Olip-Tags are snap-on markers which slip easily on wire and cable. Markers are non-adhesive and come on a plastic wand for trouble free installation. |
| | Interlocking design of these markers help to keep them aligned and readable. |
| | Clip-Tags have an opening on one end which means that they can be used on pre-terminated and pre-installed wires attached to terminal blocks. |
| Product Description | ClipTags are "open" markers that has an open end which can be snapped over pre-terminated cables. Each legend is |
| | printed black on white and has a very low profile when applied to wire and cable. Available in printed legends 0 to 9, + and -, each package contains 300 pieces. |
| Short Description | |
| Product Dimensions | |
| Length L (Imperial) | 0.131 " |
| Length L (Metric | 3.35 mm |
| Outside Diameter Min. (Imperial) | 0.128 " |
| Outside Diameter Min. (Metric |) 3.25 mm |
| Outside Diameter Max. (Imperial) | 0.177 " |
| Outside Diameter Max. (Metric |) 4.50 mm |
| Logistics and Packaging | |
| Quantity Per | pack |
| Package Quantity | / 300 |
| Package Quantity (Metric | 300 |
| Carton Quantity | / 300 |
| Material and Specifications | |
| Materia | Polyamide 6.6 (PA66) |
| Material Shortcur | |
| Operating Temperature | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complian | |
| | |
| | |