

109-00111



Article Number: 109-00111

Q Tie, 11.8" Long, 120lb Tensile Strength, PA66HS, Black, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 109-00111

Type Q120I

Color Black (BK)

- Features and Benefits**
- Open-head design with easily detectable slot opening allows for swift and easy insertion
 - Pre-lock feature allows for a temporary hold
 - The large ribbed tail permits an ergonomic installation
 - Two rails on the strap ensure guidance through the cable tie head

Product Description Q Ties have a distinctive open-style head, a pre-lock function, and a large ribbed tail. The easily detectable slot opening offered with the tail and tie head offers ease of placement especially when working with gloves is necessary or for blind applications with limited view of the installation. The pre-lock feature allows for temporary holding of cable and wire bundles, permitting additional cables and wires to be placed without destroying the cable tie. Q Ties can be tensioned by hand or with one of HellermannTyton's mechanical cable tie application tools.

Short Description Q Tie, 11.8" Long, 120lb Tensile Strength, PA66HS, Black, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 530 N

Length L (Imperial) 11.8 "

Length L (Metric) 300 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.3 "

Width W (Metric) 7.7 mm

Cable Tie Width Max. (Imperial) 0.303 "

Cable Tie Width Max. (Metric) 7.7 mm

Bundle Diameter Min. (Imperial) 0.12 "

Bundle Diameter Min. (Metric) 6.0 mm

Bundle Diameter Max. (Imperial) 2.8 "

Bundle Diameter Max. (Metric) 70.0 mm

Thickness T (Imperial) 0.07 "

Cable Tie Head Length (Imperial) 0.425 "

Cable Tie Head Width (Imperial) 0.52 "

Thickness T (Metric) 1.8 mm

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 100 Pieces
Carton Quantity 2000 Pieces

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut PA66HS
Flammability UL94 V2
Halogenfree Yes
Operating Temperature -40°F to +221°F (-40°C to +105°C)
ROHS Compliant Yes
Certification/Specification UL62275