

111-12300



Article Number: 111-12300

Heavy Duty Cable Tie, 9.1" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 300/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 111-12300

Type WSS

Color Black (BK)

- Features and Benefits**
- Wider and thinner strap design increases flexibility, provides low insertion and minimizes pinching of bundles.
 - Low profile head with clamping rails provide compact bundling with a full circumferential compression around bundles.
 - Bent tail allows for quick insertion into head or mounts.
 - High impact, heat and UV stabilized heavy duty cable ties contain an impact modifier allowing greater flexibility and greater resistance to vibration.

Product Description The Heavy Duty Wide Strap Cable Tie was designed to minimize the pinching of soft bundles and the potential of lateral movement along the bundle. The low profile head and underside clamping rails increase the grip around the bundle and provide a better fit than traditional cable ties. These are used primarily in the trucking and heavy equipment industries, but can be used in a wide variety of applications where strength is needed.

Short Description Heavy Duty Cable Tie, 9.1" Long, 120lb Tensile Strength, PA66HIRHSUV, Black, 300/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 535.0 N

Length L (Imperial) 9.1 "

Length L (Metric) 231.0 mm

Fixation Method None

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.38 "

Bundle Diameter Min. (Metric) 9.7 mm

Bundle Diameter Max. (Imperial) 2.3 "

Bundle Diameter Max. (Metric) 58.4 mm

Thickness T (Imperial) 0.055 "

Cable Tie Head Length (Imperial) 0.393 "

Cable Tie Head Width (Imperial) 0.78 "

Thickness T (Metric) 1.4 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	300 Pieces
Carton Quantity	1200
Weight (Metric)	1.8 kg

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Flammability	UL94 HB
Operating Temperature	-40°F to +230°F (-40°C to +110°C)
ROHS Compliant	Yes