

118-05900



Article Number: 118-05900

Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 118-05900

**Type** T50LOS

**Color** Black (BK)

- Features and Benefits**
- Outside serrations minimize damage to cables, while still providing high tensile strength and low insertion force.
  - Contour style head design provides additional space in constrained areas.
  - Heat stabilized material provides excellent resistance to high heat exposures.

**Product Description** HellermannTyton outside serrated cable ties are designed with a smooth inside surface to help minimize indentation or damage to wire and cable insulation, while offering high tensile strength and low insertion force. The contour style head takes up less space than traditional style cable ties making it ideal for space constrained areas. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

**Short Description** Outside Serrated Cable Tie, 15" Long, 50lb Tensile Strength, PA66HS, Black, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225.0 N

**Length L (Imperial)** 15.0 "

**Length L (Metric)** 384.0 mm

**Fixation Method** None

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Height H (Imperial)** 0.051 "

**Height H (Metric)** 1.3 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.6 mm

**Bundle Diameter Max. (Imperial)** 4.3 "

**Bundle Diameter Max. (Metric)** 110.0 mm

**Thickness T (Imperial)** 0.05 "

**Cable Tie Head Length (Imperial)** 0.26 "

**Cable Tie Head Width (Imperial)** 0.31 "

**Thickness T (Metric)** 1.3 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100 Pieces
<b>Carton Quantity</b>	4000 Pieces
<b>Weight (Metric)</b>	4 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Halogenfree</b>	Yes
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	PAN6481