

121-63560

Article Number: 121-63560

Kabelrap Tie, 14" Long, 110lb Tensile Strength, PA66UV, Black, 50/pkg

HellermannTyton



Download drawing



Download spec sheet

Base Data

Local Order Number 121-63560

Type KR6/35

Color Black (BK)

Features and Benefits

- Kabelrap tie offers a smooth strap providing secure assembly without damaging cables or hoses.
- Curved head design provides full circumferential compression which offers vibration resistance.

Product Description The patented Kabelrap cable tie design offers a smooth strap which is locked into place with a glass fiber reinforced pin. The curved head design provides full circumferential compression around the bundle or harness. Once applied with the required KR6/8 manual tool, the tie offers a secure and vibration resistant assembly.

Short Description Kabelrap Tie, 14" Long, 110lb Tensile Strength, PA66UV, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 110.0 lbs

Minimum Tensile Strength (Metric) 490.0 N

Length L (Imperial) 14.0 "

Length L (Metric) 360 mm

Fixation Method Connector Clip

Releasable Closure No

Tie Closure fibreglass pin

Variant No Serration

Width W (Imperial) 0.24 "

Width W (Metric) 6.1 mm

Cable Tie Width Max. (Imperial) 0.25 "

Cable Tie Width Max. (Metric) 6.4 mm

Bundle Diameter Min. (Imperial) 0.19 "

Bundle Diameter Min. (Metric) 4.7 mm

Bundle Diameter Max. (Imperial) 3.7 "

Bundle Diameter Max. (Metric) 93.0 mm

Thickness T (Imperial) 0.06 "

Cable Tie Head Width (Imperial) 0.37 "

Thickness T (Metric) 1.6 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 2500 Pieces

Weight (Metric) 3.17 kg

Material and Specifications

Material Polyamide 6.6 UV-resistant (PA66UV)

Material Shortcut PA66UV

Flammability UL94 V2

Operating Temperature -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

Certification/Specification GL