

121-83360



Article Number: 121-83360

Kabelrap Tie, 13.3" Long, 176lb Tensile Strength, PA66UV, Black, 50/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 121-83360

Type KR8/33

Color Black (BK)

Features and Benefits

- Kabelrap tie offers a smooth strap providing secure assembly without damaging cables or hoses.
- Curved head design provides full circumferential compression which offers vibration resistance.

Product Description The patented Kabelrap cable tie design offers a smooth strap which is locked into place with a glass fiber reinforced pin. The curved head design provides full circumferential compression around the bundle or harness. Once applied with the required KR6/8 manual tool, the tie offers a secure and vibration resistant assembly.

Short Description Kabelrap Tie, 13.3" Long, 176lb Tensile Strength, PA66UV, Black, 50/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 176.0 lbs

Minimum Tensile Strength (Metric) 785.0 N

Length L (Imperial) 13.3 "

Length L (Metric) 337.0 mm

Fixation Method Connector Clip

Releasable Closure No

Tie Closure fibreglass pin

Variant No Serration

Width W (Imperial) 0.32 "

Width W (Metric) 8.0 mm

Bundle Diameter Min. (Imperial) 0.32 "

Bundle Diameter Min. (Metric) 8.0 mm

Bundle Diameter Max. (Imperial) 3.4 "

Bundle Diameter Max. (Metric) 86.0 mm

Thickness T (Imperial) 0.091 "

Cable Tie Head Length (Imperial) 0.31 "

Cable Tie Head Width (Imperial) 0.46 "

Thickness T (Metric) 2.3 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 50 Pieces

Carton Quantity 1500 Pieces

Weight (Metric) 4.43 kg

Material and Specifications

Material	Polyamide 6.6 UV-resistant (PA66UV)
Material Shortcut	PA66UV
Flammability	UL94 V2
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes
Certification/Specification	GL