# HellermannTyton

### 126-00000

126-00000		
C	rticle Number: 126-00000 able Tie and Edge Clip, 50 lbs, 8" Long, EC13, Panel Thickness .04"12", PA66HS, Black, 500/bag	
Download drawing Download	d spec sheet	
Local Order Number	126-00000	
Туре	T50SOSEC13E	
Color	Black (BK)	
Features and Benefits	<ul> <li>Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.</li> <li>Edge Clip provides low insertion force and high extraction force ideal for assembly environments.</li> <li>Two piece assembly allows the mount to slide along the strap ensuring proper orientation.</li> <li>Cable tie is outside serrated to reduce bundle chafing.</li> </ul>	
Product Description	The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.	

## Short Description Cable Tie and Edge Clip, 50 lbs, 8" Long, EC13, Panel Thickness .04"-.12", PA66HS, Black, 500/bag

Product Dimensions	
Minimum Tensile Strength (Imperial)	50.0 lbs
Minimum Tensile Strength (Metric)	180 N
Length L (Imperial)	6.0 "
Length L (Metric)	160.0 mm
Length L2 (Imperial)	0.6 "
Length L2 (Metric)	15.0 mm
Fixation Method	Edge Clips
Identification Plate Position	none
Releasable Closure	No
Tie Closure	plastic pawl
Variant	Outside Serrated
Width W (Imperial)	0.18 "
Width W (Metric)	4.6 mm
Width W2 (Imperial)	0.43 "
Width W2 (Metric)	11.0 mm
Height H (Imperial)	0.06 "
Height H (Metric)	1.35 mm
Height H2 (Imperial)	0.591 "
Bundle Diameter Min. (Imperial)	0.04 "
Bundle Diameter Min. (Metric)	1.0 mm
Bundle Diameter Max. (Imperial)	1.4 "

Bundle Diameter Max. (Metric)	35.0 mm
Panel Thickness Max. (Imperial)	0.12 "
Panel Thickness Max. (Metric)	3.0 mm
Panel Thickness Min. (Imperial)	0.04 "
Panel Thickness Min. (Metric)	1.0 mm
Thickness T (Imperial)	0.05 "
Thickness T (Metric)	1.35 mm

### Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500 Pieces
Carton Quantity	5000 Pieces

Weight (Metric) 1.95 kg

### Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS)
Material Shortcut	PA66HS
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
<b>ROHS</b> Compliant	Yes

© HellermannTyton 2015