

126-00015



**Article Number: 126-00015**

**Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 126-00015

**Type** T50SDOP

**Color** Black (BK)

- Features and Benefits**
- Part is easy to install without the need for a tool.
  - Design provides low insertion and high extraction force.
  - The oval design helps prevent the part from twisting.

**Product Description** HellermannTyton's dome push in tie with arrowhead locks into place between the fixing and the head of the cable tie. This covers the hole and minimizes the ingress of dust, dirt, and water. The anchor adjusts for variations in panel thickness, which ensures a secure fixing at all times. The oval design helps prevent the part from twisting.

**Short Description** Domed Push Mount Tie, 6.3" Long, Fixing Hole Diameter .24" - .48", PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 6.3 "

**Length L (Metric)** 160.0 mm

**Fixation Method** Arrowhead for oval holes

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.2 "

**Width W (Metric)** 5.0 mm

**Height H (Imperial)** 0.36 "

**Bundle Diameter Min. (Imperial)** 0.2 "

**Bundle Diameter Min. (Metric)** 5.0 mm

**Bundle Diameter Max. (Imperial)** 1.2 "

**Bundle Diameter Max. (Metric)** 30.0 mm

**Disc Diameter (Imperial)** 0.87 "

**Disc Diameter (Metric)** 22.0 mm

**Panel Thickness Max. (Imperial)** 0.08 "

**Panel Thickness Max. (Metric)** 1.9 mm

**Panel Thickness Min. (Imperial)** 0.04 "

**Panel Thickness Min. (Metric)** 1.0 mm

<b>Mounting Hole Diameter D (Imperial)</b>	0.24 - 0.48 "		
<b>Mounting Hole Diameter D (Metric)</b>	6.2 x 12.2 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.244 "	<b>Mounting Hole Diameter D Max.0.48 "</b>	
		<b>(Imperial)</b>	<b>Stud Length min (metric)9.2 mm</b>
<b>Thickness T (Imperial)</b>	0.05 "		
<b>Thickness T (Metric)</b>	1.3 mm		

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500 Pieces
<b>Carton Quantity</b>	4000 Pieces
<b>Weight (Metric)</b>	1.7 kg

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes