

126-00041

Article Number: 126-00041

Arrowhead Wing Push Mount Tie, 4.5" Long, 18lb, Panel Thickness 0.19"-0.22", PA66, Natural, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 126-00041

**Type** T18RWPM

**Color** Natural (NA)

- Features and Benefits**
- Easy and quick insertion ideal for production environment.
  - Tie "clicks" into place upon final installation signaling installer insertion is complete.
  - Arrowhead style mount provides low insertion and high extraction force.

**Product Description** Arrowhead Wing Push Ties design helps stabilize the tie in high vibration applications. This can be used on sheet metal, wood, and cast iron.

**Short Description** Arrowhead Wing Push Mount Tie, 4.5" Long, 18lb, Panel Thickness 0.19"-0.22", PA66, Natural, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 18.0 lbs

**Minimum Tensile Strength (Metric)** 80 N

**Length L (Imperial)** 4.5 "

**Length L (Metric)** 113.0 mm

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.1 "

**Width W (Metric)** 2.5 mm

**Width W2 (Imperial)** 0.25 "

**Width W2 (Metric)** 6.4 mm

**Height H (Imperial)** 0.23 "

**Height H (Metric)** 5.8 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 0.87 "

**Bundle Diameter Max. (Metric)** 22.2 mm

**Disc Diameter (Imperial)** 0.5 "

**Disc Diameter (Metric)** 13.1 mm

**Panel Thickness Max. (Imperial)** 0.13 "

<b>Panel Thickness Max. (Metric)</b>	3.2 mm		
<b>Panel Thickness Min. (Imperial)</b>	0.06 "		
<b>Panel Thickness Min. (Metric)</b>	1.52 mm		
<b>Mounting Hole Diameter D (Imperial)</b>	0.19 - 0.22 "		
<b>Mounting Hole Diameter D (Metric)</b>	4.8 - 5.6 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.19 "		
		<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.22 "
			<b>Thickness T (Imperial)</b>
			0.043 "
<b>Mounting Hole Diameter D Max. (Metric)</b>	5.6 mm		
		<b>Mounting Hole Diameter D Min. (Metric)</b>	4.8 mm
<b>Thickness T (Metric)</b>	1.1 mm		

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100
<b>Carton Quantity</b>	10000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 (PA66)
<b>Material Shortcut</b>	PA66
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +185°F (-40°C to +85°C)
<b>ROHS Compliant</b>	Yes
<b>Certification/Specification</b>	UL