

126-00043

Article Number: 126-00043

Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66, Natural, 100/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 126-00043

Type T50SSF

Color Natural (NA)

- Features and Benefits**
- Quick and easy mounting will save time.
 - Tie is releasable and reusable providing a cost savings.
 - Design provides low insertion and high extraction force.

Product Description Push Mount Ties provide a one piece, all plastic tie for quick and simple cable mounting.

Short Description Push Mount Tie, 6" Long, 50lb Tensile, Panel Thickness .04"-.14", PA66, Natural, 100/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 6.25 "

Length L (Metric) 159.0 mm

Fixation Method Arrowhead

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.19 "

Width W (Metric) 4.7 mm

Height H (Imperial) 0.3 "

Height H (Metric) 7.5 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.5 mm

Bundle Diameter Max. (Imperial) 1.4 "

Bundle Diameter Max. (Metric) 35.0 mm

Panel Thickness Max. (Imperial) 0.14 "

Panel Thickness Max. (Metric) 3.56 mm

Panel Thickness Min. (Imperial) 0.04 "

Panel Thickness Min. (Metric) 1.00 mm

Mounting Hole Diameter D (Metric) 6.4 - 7.1 mm

Mounting Hole Diameter D Min. 0.25 "

(Imperial) Mounting Hole Diameter D Max.0.28 "
(Imperial)

Mounting Hole Diameter D Max.7.1 mm
(Metric)6.4 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag
Package Quantity (Metric) 100
Carton Quantity 5000

Material and Specifications

Material Polyamide 6.6 (PA66)
Material Shortcut PA66
Flammability UL94 V2
Operating Temperature -40°F to +185°F (-40°C to +85°C)
ROHS Compliant Yes