

126-00049



Article Number: 126-00049

Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 126-00049

**Type** T50SSFM

**Color** Black (BK)

- Features and Benefits**
- Wing design helps stabilize the tie in high vibration applications.
  - Includes a ladder type strap as opposed to a conventional serrated strap; giving the benefit of being extra flexible.
  - Wing design provides low insertion and high extraction force.

**Product Description** Wing Push Mount Ties' supporting legs ensure a firm and secure fixing for bundles. These legs also reduce vibration in panel thickness enabling one part to suit many different applications such as sheet metal, wood, and cast iron.

**Short Description** Wing Push Mount Tie, 6.0" Long, 50lb Tensile, PA66HIRHS, Black, 500/bag

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 6.3 "

**Length L (Metric)** 160.0 mm

**Fixation Method** Arrowhead

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.6 "

**Width W2 (Metric)** 14.7 mm

**Height H (Imperial)** 0.2 "

**Height H (Metric)** 5.6 mm

**Bundle Diameter Min. (Imperial)** 0.06 "

**Bundle Diameter Min. (Metric)** 1.5 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Panel Thickness Max. (Imperial)** 0.12 "

**Panel Thickness Max. (Metric)** 3.0 mm

**Panel Thickness Min. (Imperial)** 0.03 "

<b>Panel Thickness Min. (Metric)</b>	0.7 mm		
<b>Mounting Hole Diameter D (Metric)</b>	6.0 - 6.6 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.24 "	<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.25 "
		<b>Mounting Hole Diameter D Max. (Metric)</b>	6.6 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>			6.0 mm

## Logistics and Packaging

---

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500
<b>Carton Quantity</b>	5000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +230°F (-40°C to +110°C)
<b>ROHS Compliant</b>	Yes