

151-00432



Article Number: 151-00432

VHB Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, Black, 100/pkg



Download spec sheet

Base Data

Local Order Number 151-00432

Type MB3APT

Color Black (BK)

- Features and Benefits**
- Secures with a high temperature, VHB adhesive backing for heavy bonding applications.
 - Can also be secured using two or four screws; providing multiple options.
 - For use with 18 and 30 pound cable ties to provide stability when securing bundles.
 - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

Product Description HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

Short Description VHB Adhesive Bases, .14" Max tie width, .75" Length/Width, .12" Hole Dia., PA66, Black, 100/pkg

Product Dimensions

Length L (Imperial) 0.75 "

Length L (Metric) 19.0 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 0.75 "

Width W (Metric) 19.0 mm

Cable Tie Width Max. (Imperial) 0.14 "

Cable Tie Width Max. (Metric) 4.1 mm

Height H (Imperial) 0.18 "

Height H (Metric) 3.8 mm

Mounting Hole Diameter D (Imperial) 0.12 "

Mounting Hole Diameter D (Metric) 3.1 mm

Mounting Hole Centers (Imperial) 0.52 "

Mounting Hole Diameter D Max. (Metric) 3.1 mm

Mounting Hole Diameter D Min. (Metric) 3.1 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100 Pieces

Carton Quantity 10000 Pieces

Weight (Metric) 1.6 kg

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66
Adhesive	Acrylate with base of acrylic foam
Adhesive Shortcut	mod. Acrylate
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Flammability	UL94 V2 (excluding adhesive)
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes