

151-00810



Article Number: 151-00810

Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66UV, Black, 100/pkg



Download spec sheet

## Base Data

Local Order Number 151-00810

Type MB4A

Color Black (BK)

- Features and Benefits**
- For use with 18 and 30 pound cable ties to provide stability when securing bundles.
  - Secures with rubber based adhesive backing and/or two or four screws.
  - 4 way opening allows cable ties to be installed parallel or perpendicular to wire bundles.

**Product Description** HellermannTyton adhesive fastened mounting bases are used with 18 through 150 pound cable ties to provide stability when securing bundles. The mounts are installed using the adhesive backing and/or by securing two or four screws. The 4 way opening allows the cable ties to be inserted parallel or perpendicular to the wire bundles.

**Short Description** Acrylic Adh. Bases, .18" Max tie width, 1.12" Length/Width, .18" Hole Dia., PA66UV, Black, 100/pkg

## Product Dimensions

Length L (Imperial) 1.12 "

Length L (Metric) 28.5 mm

Fixation Method Screw Mounting and Adhesive

Width W (Imperial) 1.12 "

Width W (Metric) 28.5 mm

Cable Tie Width Max. (Imperial) 0.18 "

Cable Tie Width Max. (Metric) 4.6 mm

Height H (Imperial) 0.23 "

Height H (Metric) 5.8 mm

Mounting Hole Diameter D (Imperial) 0.18 "

Mounting Hole Diameter D (Metric) 4.6 mm

Mounting Hole Centers (Imperial) 0.8 "

Mounting Hole Diameter D Max. (Metric) 4.6 mm

Mounting Hole Diameter D Min. (Metric) 4.6 mm

## Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 100

## Material and Specifications

Material Polyamide 6.6 UV-stabilized (PA66UV)

Material Shortcut PA66UV

**Flammability** UL94 V2 (excluding adhesive)

**Operating Temperature** -40°F to +185°F (-40°C to +85°C)

**ROHS Compliant** Yes

**UL Listed (US and Canada)** No

**UL Recognized (US and Canada)** Yes