

151-00814

Article Number: 151-00814

H-Mount for .75" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 151-00814
Type HM7
Color Black (BK)

Features and Benefits

- H-Mounts utilize existing frame rail bolts eliminating the need for additional fasteners.
- When used with cable ties, the H-Mounts eliminate the need to carry multiple sizes of fixed bundle diameter clamps which reduces inventory and purchasing costs.
- Ability to position bundles in up to three locations, provides multiple use options.

Product Description H-mounts offer a secure bundling solution that utilizes existing frame rail bolts which reduces component costs and improves installation time. The H-mounts have three bundle mounting locations each accommodating ties up to 1/2" wide. The top tie slot allows the bundle to be positioned directly over the bolt. The two curved tie slots on the sides position the bundles adjacent to the bolt yet away from the frame.

Short Description H-Mount for .75" standard bolts and Huck-Spin bolts, PA66HIRHSUV, Black, 900/pkg

Product Dimensions

Length L (Imperial) 2.0 "
Length L (Metric) 50.0 mm
Fixation Method thread-bolt
Width W (Imperial) 1.0 "
Width W (Metric) 26.0 mm
Cable Tie Width Max. (Imperial) 0.052 "
Cable Tie Width Max. (Metric) 13.2 mm
Height H (Imperial) 1.1 "
Height H (Metric) 28.0 mm
Stud Size (Imperial) 0.75 "
Stud Size (Metric) 19.0 mm

Logistics and Packaging

Quantity Per box
Package Quantity (Metric) 900
Carton Quantity 900

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut PA66HIRHSUV
Flammability UL94 HB

Operating Temperature -65°F to +212°F (-54°C to +100°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US) No