HellermannTyton

151-01106

A	rticle Number: 151-01106
۲ ۲	ligh Torque Axial Mount, Bolt Hole Dia .510 in, PA66HIRHS, Black, 500/pkg
	RoHS
Download drawing	
Download drawing 📃 Downloa	id spec sheet
Base Data	
Local Order Number	r 151-01106
Туре	sAM500B
Color	r Black (BK)

Features and Benefits	 Positions bundles off cross members and frame rails to prevent abrasion and chafing. Metal insert bushing accommodates high torque installation. Made with high impact, heat stabilized, and UV material ideal for trucking and heavy equipment environments.
Product Description	HellermannTyton's axial oval mount stands off bundles from frame rails and cross members to prevent them from rubbing and chafing. The axial oval mount accommodates cable ties up to 0.5" wide. The hole on the mount was designed to fit a 5/16" bolt.
Fixation Method (FF)	Screw Mounting and Rivet
Short Description	High Torque Axial Mount, Bolt Hole Dia .510 in, PA66HIRHS, Black, 500/pkg

Product Dimensions

Length L (Imperial)	1.18 "
Length L (Metric)	29.87 mm
Width W (Imperial)	0.96 "
Width W (Metric)	24.32 mm
Height H (Imperial)	1.77 "
Height H (Metric)	44.86 mm
Bundle Diameter Max. (Imperial)	2.0 "
Bundle Diameter Max. (Metric)	50.8 mm
Mounting Hole Diameter D (Imperial)	0.51 "
Mounting Hole Diameter D (Metric)	12.95 mm

Logistics and Packaging

Quantity PerbagPackage Quantity (Metric)500

Material and Specifications

Material	Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HIRHS
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS compliant (Article 4 - 1)	Yes

© HellermannTyton 2015