

151-06500



Article Number: 151-06500

Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter 0.25"-3.0", Black, PA66HS, 2200/pkg



Download spec sheet

## Base Data

Local Order Number 151-06500

Type DSWS4

Color Black (BK)

**Features and Benefits**

- "H" profile of the saddles allows for broad surface contact with the bundle, which minimizes pinching and crushing of the bundle.
- Swivels in 360 degree motion to accommodate any area.
- Accommodates T50-T250 ties to handle both light duty and heavy duty applications.

**Product Description** These saddle spacers are installed between two bundles (such as wires, cables, hoses, tubing, conduit, etc.) to separate and prevent chafing and wear. The mounts can be easily rotated by hand, allowing the bundles to be crossed and rotated at any angle. Cable ties, which secure the bundles, are used with the mounts. The dual swivel saddle spacers accommodate cable ties up to 1/2" wide

**Short Description** Dual Swivel Saddle Spacer for T50-T250, Bundle Diameter 0.25"-3.0", Black, PA66HS, 2200/pkg

## Product Dimensions

Length L (Imperial) 0.91 "

Length L (Metric) 23.6 mm

Width W (Imperial) 0.8 "

Width W (Metric) 20.3 mm

Height H (Imperial) 0.7 "

Height H (Metric) 18.0 mm

Bundle Diameter Min. (Imperial) 0.3 "

Bundle Diameter Min. (Metric) 6.0 mm

Bundle Diameter Max. (Imperial) 3.0 "

Bundle Diameter Max. (Metric) 76.0 mm

## Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 2200 Pieces

Weight (Metric) 3.8 kg

## Material and Specifications

**Material** Polyamide 6.6 heat stabilized (PA66HS)  
Polyacetal (POM)

**Material Shortcut** POM  
PA66HS

**Flammability** UL94 HB

**Minimum Extraction Force (Imperial)** 100.0 lbs

**Minimum Extraction Force (Metric)** 445 N

**Operating Temperature** -31°F to +185°F (-35°C to +85°C)  
-40°F to +221°F (-40°C to +105°C)

**ROHS compliant (Article 4 - 1)** Yes