HellermannTyton

151-10905

Article Number: 151-10905

Q Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, White, 100/bag

✓ RoHS

📄 Download drawing   📄 Download spec sheet

Base Data

Local Order Number	151-10905
Type	QM30A
Color	Natural (NA)
Features and Benefits	• 2- or 4-way entry options for the Q Tie, offering flexibility and stability
Product Description	Q Mounts are designed to work exclusively with the Q Tie cable tie series. This mounting component is available with adhesive or can be secured with screws. The Q Mount allows either a 2- or 4-way entry for the Q Tie, providing a quick and simple insertion into the mount. Once in place, the Q Tie will not slip out, even in vertical mounting applications.
Short Description	Q Mount with Adhesive, 1.2" x 1.2" x 0.21", 4 way entry for Q18 thru Q50 ties, PA66, White, 100/bag

Product Dimensions

Length L (Imperial)	1.2 "
Length L (Metric)	30.0 mm
Fixation Method	Screw Mounting and Adhesive
Width W (Imperial)	1.2 "
Width W (Metric)	30.0 mm
Cable Tie Width Max. (Imperial)	0.2 "
Cable Tie Width Max. (Metric)	5.1 mm
Height H (Imperial)	0.21 "
Height H (Metric)	4.5 mm
Mounting Hole Diameter D (Imperial)	0.16 "
Mounting Hole Diameter D (Metric)	4.1 mm
Mounting Hole Diameter D Min. (Imperial)	0.16 "
Mounting Hole Centers (Imperial)	0.83 "
Mounting Hole Diameter D Max. (Metric)	4.1 mm
Mounting Hole Diameter D Min. (Metric)	4.1 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	100 Pieces

Material and Specifications

Material	Polyamide 6.6 (PA66)
Material Shortcut	PA66

Adhesive Shortcut	Synthetic rubber T60
Adhesive	Synthetic rubber with base of polyethylene foam
Adhesive Operating Temperature	-40°F to +140°F (-40°C to +60°C)
Flammability	UL94 V2 (excluding adhesive)
Halogenfree	Yes
Operating Temperature	-40°F to +185°F (-40°C to +85°C)
ROHS Compliant	Yes