

155-12300

Article Number: 155-12300

Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 155-12300

**Type** T50S0SSBS5E

**Color** Black (BK)

**Features and Benefits**

- Oval mount design pushes on easy by hand without the need for tools.
- Design provides low insertion and high extraction force.

**Product Description** The special oval shape provides for an approximate .20" (5.0 mm) lateral adjustment, allowing for any misalignment of the stud or incorrect positioning of the tie on the cables

**Short Description** Oval Stud Mount Cable Tie, Designed for 5.0 mm stud, 6.0 Long, PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 160.0 mm

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Outside Serrated

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Width W2 (Imperial)** 0.5 "

**Width W2 (Metric)** 12.0 mm

**Height H (Imperial)** 0.06 "

**Height H (Metric)** 1.35 mm

**Height H2 (Imperial)** 0.6 "

**Height H2 (Metric)** 15 mm

**Bundle Diameter Min. (Imperial)** 0.04 "

**Bundle Diameter Min. (Metric)** 1.0 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Thickness T (Imperial)** 0.05 "

**Thickness T (Metric)** 1.35 mm

**Stud Size (Imperial)** 0.2 "

**Stud Size (Metric)** 5.0 mm

## Logistics and Packaging

---

**Quantity Per** bag

**Package Quantity (Metric)** 500 Pieces

**Carton Quantity** 4000 Pieces

**Weight (Metric)** 2.85 kg

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS Compliant** Yes