

155-30602



Article Number: 155-30602

Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 155-30602

**Type** T50SSBS50TE

**Color** Black (BK)

- Features and Benefits**
- Design gives quick and easy assembly by hand without the need for tools.
  - Mount can be used in a wide variety of applications where 5mm weld studs or 5mm ISO bolts.
  - Design provides low insertion force and high extraction force.

**Product Description** The Standoff Stud Mount tie applies easily to weld studs and secures bundles away from fixing holes. These are used primarily in the automotive industry, but can be used in a variety of applications.

**Short Description** Standoff Stud Mount Tie, 5.0 mm studs, 6.0" Long, PA66HS, Black, 500/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 200 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 160 mm

**Fixation Method** Weld Stud Fixing

**Identification Plate Position** none

**Releasable Closure** No

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.0 mm

**Bundle Diameter Min. (Imperial)** 0.16 "

**Bundle Diameter Min. (Metric)** 4.0 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Stud Length Max. (Imperial)** 0.65 "

**Stud Length Max. (Metric)** 16.5 mm

**Thickness T (Imperial)** 0.05 "

**Thickness T (Metric)** 1.35 mm

**Stud Size (Imperial)** 0.2 "

**Stud Size (Metric)** 5.0 mm

## Logistics and Packaging

---

**Quantity Per** bag  
**Package Quantity (Metric)** 500 Pieces  
**Carton Quantity** 4000 Pieces  
**Weight (Metric)** 2.3 kg

---

## Material and Specifications

**Material** Polyamide 6.6 heat stabilized (PA66HS)  
**Material Shortcut** PA66HS  
**Flammability** UL94 V2  
**Operating Temperature** -40°F to +221°F (-40°C to +105°C)  
**ROHS Compliant** Yes