

155-31202



**Article Number: 155-31202**

**Wire and Swivel Clip Tie, 50lb, Diameter .17"-.19", 6.0" Long, PA66HS, Black, 500/Pkg**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 155-31202

**Type** T50SVC5

**Color** Black (BK)

- Features and Benefits**
- Design provides quick and easy installation by hand without the need for tools.
  - Multiple bundle diameters available for all different ranges of bundles.
  - Clip allows 360 degrees of rotation to attach in any orientation.

**Product Description** HellermannTyton's simple to use fixing tie allows the attaching of wires or hoses to an existing harness. This allows 360 degree rotation, and the ability to be oriented in any direction in relation to the main harness. This is ideally suited for any application in which the wire or hose can move in relation to the fixing point.

**Fixation Method (FF)** Omega Clips

**Identification Plate Position** none

**Releasable Closure (Yes/No)** No

**Short Description** Wire and Swivel Clip Tie, 50lb, Diameter .17"-.19", 6.0" Long, PA66HS, Black, 500/Pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 222 N

**Length L (Imperial)** 6.0 "

**Length L (Metric)** 155 mm

**Attaches to Diameter (Imperial)** 0.17" - 0.2"

**Width W (Imperial)** 0.19 "

**Width W (Metric)** 4.7 mm

**Bundle Diameter Min. (Imperial)** 0.04 "

**Bundle Diameter Min. (Metric)** 1.0 mm

**Bundle Diameter Max. (Imperial)** 1.4 "

**Bundle Diameter Max. (Metric)** 35.0 mm

**Mounting Hole Diameter D (Imperial)** 0.17 - 0.19 "

**Thickness T (Imperial)** 0.05 "

**Attaches to Diameter (Metric)** 4.5 - 5.2

**Thickness T (Metric)** 1.35 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity (Metric)** 500

**Carton Quantity** 5000 Pieces

**Weight (Metric)** 1.47 kg

## Material and Specifications

---

**Material** Polyamide 6.6 heat stabilized (PA66HS)

**Material Shortcut** PA66HS

**Flammability** UL94 V2

**Operating Temperature** -40°F to +221°F (-40°C to +105°C)

**ROHS compliant (Article 4 - 1)** Yes