

155-32602



Article Number: 155-32602

Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack



Download drawing



Download spec sheet

Base Data

Local Order Number 155-32602

Type FT6LG.M.St.Aufn.II

Color Black (BK)

Features and Benefits Connector Clips provide a simple and easy method for mounting connectors to a mounting surface in a variety of applications. HellermannTyton offers connector clips with robust and detailed designs that include anti-rattle disc features, anti-rotation oval fir trees, and clamps for mounting on edges. HellermannTyton offers an assortment of connector clips that are available for a variety of connector slot designs found on most of the largest global connector manufacturers.

Short Description Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack

Product Dimensions

Fixation Method Fir Tree

Length of Fir Tree 11.1 mm

Disc Diameter (Imperial) 0.63 "

Disc Diameter (Metric) 16 mm

Panel Thickness Max. (Imperial) 0.2 "

Panel Thickness Max. (Metric) 5.0 mm

Panel Thickness Min. (Imperial) 0.03 "

Panel Thickness Min. (Metric) 0.75 mm

Mounting Hole Diameter D (Imperial) 0.26-0.28 "

Mounting Hole Diameter D (Metric) 6.5 - 7.0 mm

Mounting Hole Diameter D Min. (Imperial) 0.26 "

Mounting Hole Diameter D Max.0.28 "
(Imperial)

Mounting Hole Diameter D Max.7.0 mm
(Metric) 6.5 mm

Mounting Hole Diameter D Min. (Metric)

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 15000 Pieces

Weight (Metric) 0.8 kg

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HIRHS

Flammability UL94 HB

Operating Temperature -40°F to +221°F (-40°C to +105°C)

ROHS Compliant Yes