

156-00068



Article Number: 156-00068

Heavy Duty Fir Tree with Cable Tie, 9" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-00068

**Type** WSSFT9A

**Color** Black (BK)

- Features and Benefits**
- The "H" profile provides a broad surface contact to minimize the pinching of bundles.
  - Heavy duty fir tree mounts are equipped with a friction tab that will hold the tie in the mount, allowing them to be preassembled prior to installation.
  - Designed specifically for HellermannTyton 120 - 250 lb. cable ties for heavy duty applications.

**Product Description** HellermannTyton heavy duty fir tree mounts are designed with heavy duty applications in mind. These are optimized for up to 3 to 1 extraction versus insertion force to make assembly fast and easy. These mounts are sold as an assembly with a cable tie.

**Short Description** Heavy Duty Fir Tree with Cable Tie, 9" Length, Panel Thickness .04"-.26", PA66HIRHSUV, Black, 100/pkg

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 120.0 lbs

**Minimum Tensile Strength (Metric)** 534 N

**Length L (Imperial)** 9.0 "

**Length L (Metric)** 228.0 mm

**Fixation Method** Fir Tree

**Identification Plate Position** none

**Tie Closure** plastic pawl

**Variant** Inside Serrated

**Width W (Imperial)** 0.5 "

**Width W (Metric)** 12.7 mm

**Width W2 (Imperial)** 0.51 "

**Width W2 (Metric)** 13.0 mm

**Height H (Imperial)** 0.75 "

**Height H (Metric)** 19.1 mm

**Height H2 (Imperial)** 0.36 "

**Height H2 (Metric)** 9.0 mm

**Bundle Diameter Max. (Imperial)** 2.3 "

**Bundle Diameter Max. (Metric)** 57.0 mm

**Disc Diameter (Imperial)** 0.9 "

**Disc Diameter (Metric)** 21.6 mm

**Panel Thickness Max. (Imperial)** 0.26 "

<b>Panel Thickness Max. (Metric)</b>	6.5 mm		
<b>Panel Thickness Min. (Imperial)</b>	0.04 "		
<b>Panel Thickness Min. (Metric)</b>	1.0 mm		
<b>Mounting Hole Diameter D (Metric)</b>	8.75 - 9.25 mm		
<b>Mounting Hole Diameter D Min. (Imperial)</b>	0.34 "	<b>Mounting Hole Diameter D Max. (Imperial)</b>	0.36 "
		<b>Mounting Hole Diameter D Max. (Metric)</b>	9.25 mm
<b>Mounting Hole Diameter D Min. (Metric)</b>			8.75 mm

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	100
<b>Carton Quantity</b>	500 Pieces
<b>Weight (Metric)</b>	6.4 kg

## Material and Specifications

<b>Material</b>	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
<b>Material Shortcut</b>	PA66HIRHSUV
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-65°F to +212°F (-54°C to +100°C)
<b>ROHS Compliant</b>	Yes