

156-00306



Article Number: 156-00306

Omega Clip Tie, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38" PA66HS Tie, HIRHS MNT, BLK 500/pk



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00306

Type T50ROC1B

Color Black (BK)

Features and Benefits Omega Clips secure cables to tubular frame rails. The cable tie is fastened to the tubular frame rail and the solar cable snaps into the clip. The cable can be removed from the clip and reinstalled without additional fasteners.

Short Description Omega Clip Tie, 50lbs, Clip Dia .16"-.4" Max Bun Dia. 1.38" PA66HS Tie, HIRHS MNT, BLK 500/pk

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 7.9 "

Length L (Metric) 202 mm

Fixation Method Omega Clips

Identification Plate Position none

Tie Closure plastic pawl

Width W (Imperial) 0.181 "

Width W (Metric) 4.6 mm

Height H (Imperial) 0.05 "

Height H (Metric) 1.2 mm

Bundle Diameter Min. (Imperial) 0.16 "

Bundle Diameter Min. (Metric) 4.0 mm

Bundle Diameter Max. (Imperial) 1.8 "

Bundle Diameter Max. (Metric) 45.0 mm

Thickness T (Imperial) 0.05 "

Thickness T (Metric) 1.2 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500 Pieces

Carton Quantity 3000 Pieces

Weight (Metric) 2.6 kg

Material and Specifications

Material	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66HS PA66HIRHS
Material Cable Tie	Polyamide 6.6 heat stabilized (PA66HS)
Flammability	UL94 HB
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
ROHS Compliant	Yes