


156-00537



Article Number: 156-00537

Cable Tie and Edge Clip, 50lb, 8.0" Long, EC19, Panel Thickness .12"-.24", PA66HS, Black, 500/bag



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00537

Type T50REC19

Color Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
 - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
 - Two piece assembly allows the mount to slide along the strap ensuring proper orientation.

Product Description This cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Short Description Cable Tie and Edge Clip, 50lb, 8.0" Long, EC19, Panel Thickness .12"-.24", PA66HS, Black, 500/bag

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Minimum Tensile Strength (Metric) 225 N

Length L (Imperial) 8.0 "

Length L (Metric) 200.0 mm

Length L2 (Imperial) 0.58 "

Length L2 (Metric) 14.8 mm

Fixation Method EdgeClip, top, assembled, 2 piece

Identification Plate Position none

Variant Inside Serrated

Width W (Imperial) 0.18 "

Width W (Metric) 4.6 mm

Width W2 (Imperial) 0.6 "

Width W2 (Metric) 14.8 mm

Height H (Imperial) 0.05 "

Height H (Metric) 1.2 mm

Height H2 (Imperial) 0.7 "

Height H2 (Metric) 17.8 mm

Bundle Diameter Min. (Imperial) 0.06 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 2.0 "

Bundle Diameter Max. (Metric) 45.0 mm

Panel Thickness Max. (Imperial) 0.24 "

Panel Thickness Max. (Metric) 6.00 mm

Panel Thickness Min. (Imperial) 0.12 "

Panel Thickness Min. (Metric) 3.00 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 3000

Material and Specifications

Material Polyamide 6.6 heat stabilized (PA66HS)
Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)

Material Shortcut PA66HS

ROHS Compliant Yes