

156-00551



Article Number: 156-00551

Cable Tie and Edge Clip, 50lb, Length 200mm, EC9 Panel Thickness 1-3mm, HS Tie, HIRHS Mount, 500/pk



Download drawing



Download spec sheet

Base Data

Local Order Number 156-00551

Type T50REC9SD

Color Black (BK)

Features and Benefits

- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
- Edge Clip provides low insertion force and high extraction force ideal for assembly environments.

Product Description The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

Short Description Cable Tie and Edge Clip, 50lb, Length 200mm, EC9 Panel Thickness 1-3mm, HS Tie, HIRHS Mount, 500/pk

Product Dimensions

Minimum Tensile Strength (Imperial) 50.0 lbs

Length L (Imperial) 7.87 "

Length L (Metric) 200.0 mm

Fixation Method EdgeClip, top, assembled, 2 piece

Identification Plate Position none

Variant Inside Serrated

Height H (Imperial) 0.047 "

Height H (Metric) 1.2 mm

Bundle Diameter Min. (Imperial) 0.039 "

Bundle Diameter Min. (Metric) 1.0 mm

Bundle Diameter Max. (Imperial) 1.77 "

Bundle Diameter Max. (Metric) 45.0 mm

Panel Thickness Max. (Imperial) 0.12 "

Panel Thickness Max. (Metric) 3.00 mm

Panel Thickness Min. (Imperial) 0.039 "

Panel Thickness Min. (Metric) 1.00 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 500

Carton Quantity 4000

Material and Specifications

Material Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Polyamide 6.6 heat stabilized (PA66HS)

Material Shortcut PA66HS

Material Cable Tie Polyamide 6.6 heat stabilized (PA66HS)

Minimum Extraction Force (Imperial) 50.0 lbs

Minimum Extraction Force (Metric) 225 N

ROHS Compliant Yes