

156-00594



Article Number: 156-00594

Omega Clip Tie, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pk



Download spec sheet

Base Data

Local Order Number	156-00594
Type	T50ROC2
Color	Black (BK)
Features and Benefits	Omega Clips secure cables to tubular frame rails. The UV stabilized cable tie is fastened to the tubular frame rail and the solar cable snaps into the clip. The cable can be removed from the clip and reinstalled without additional fasteners.
Short Description	Omega Clip Tie, 50lbs, Clip Dia .26"-.3" Max Bun Dia 1.38" PA66UV Tie, HIRHS MNT, BLK 500/pk

Product Dimensions

Minimum Tensile Strength (Imperial)	50.0 lbs
Minimum Tensile Strength (Metric)	225 N
Length L (Imperial)	7.9 "
Length L (Metric)	200 mm
Fixation Method	Omega Clips
Identification Plate Position	none
Width W (Imperial)	0.18 "
Width W (Metric)	4.6 mm
Bundle Diameter Min. (Imperial)	1.8 "
Bundle Diameter Min. (Metric)	6.5 mm
Bundle Diameter Max. (Imperial)	1.8 "
Bundle Diameter Max. (Metric)	45 mm

Logistics and Packaging

Quantity Per	bag
Package Quantity (Metric)	500

Material and Specifications

Material	Polyamide 6.6 UV-stabilized (PA66UV) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
Material Shortcut	PA66UV PA66HIRHS
Material Cable Tie	Polyamide 6.6 UV-stabilized (PA66UV)
Flammability	UL94 V2
Operating Temperature	-40°F to +221°F (-40°C to +105°C) -40°F to +185°F (-40°C to +85°C)

ROHS Compliant Yes

© HellemannTyton 2015