

156-01601

Article Number: 156-01601

Rotatable Cable Tie and Edge Clip, 8.0" Length, Outside Serrated, PA66HS, Black, 500/bag



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 156-01601

**Type** CBTO50R

**Color** Black (BK)

- Features and Benefits**
- Edge Clip applies easily to plastic and metal sheets without the need for a mounting hole.
  - Edge Clip provides low insertion force and high extraction force ideal for assembly environments.
  - Cable tie is both rotatable and outside serrated to reduce bundle chafing.

**Product Description** The cable tie and edge clip assembly is ideal for use where holes are not acceptable or where adhesives will fail due to temperature problems. Edge clips are widely used for fixing and bundling cables and wires within automotive, trucking, heavy equipment, solar panel, wind power, and white goods equipment manufacturing.

**Short Description** Rotatable Cable Tie and Edge Clip, 8.0" Length, Outside Serrated, PA66HS, Black, 500/bag

## Product Dimensions

**Minimum Tensile Strength (Imperial)** 50.0 lbs

**Minimum Tensile Strength (Metric)** 225 N

**Length L (Imperial)** 8.0 "

**Length L (Metric)** 202 mm

**Length L2 (Imperial)** 0.52 "

**Length L2 (Metric)** 13.2 mm

**Fixation Method** Edge Clips with tie

**Identification Plate Position** none

**Releasable Closure** No

**Variant** Inside Serrated

**Width W (Imperial)** 0.18 "

**Width W (Metric)** 4.6 mm

**Cable Tie Width Max. (Imperial)** 0.18 "

**Cable Tie Width Max. (Metric)** 4.6 mm

**Width W2 (Imperial)** 0.5 "

**Width W2 (Metric)** 12.0 mm

**Height H (Imperial)** 0.05 "

**Height H (Metric)** 1.2 mm

**Height H2 (Imperial)** 0.6 "

**Height H2 (Metric)** 15.2 mm

**Bundle Diameter Min. (Imperial)** 0.08 "

**Bundle Diameter Min. (Metric)** 2.0 mm

<b>Bundle Diameter Max. (Imperial)</b>	1.9 "
<b>Bundle Diameter Max. (Metric)</b>	47.0 mm
<b>Panel Thickness Max. (Imperial)</b>	0.12 "
<b>Panel Thickness Max. (Metric)</b>	3.0 mm
<b>Panel Thickness Min. (Imperial)</b>	0.04 "
<b>Panel Thickness Min. (Metric)</b>	1.0 mm
<b>Thickness T (Imperial)</b>	0.05 "
<b>Thickness T (Metric)</b>	1.2 mm

---

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	500 Pieces
<b>Carton Quantity</b>	4000 Pieces
<b>Weight (Metric)</b>	4.5 kg

---

## Material and Specifications

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS) Polyamide 6.6 high impact modified, heat stabilized, UV resistant (PA66HIRHS)
<b>Material Shortcut</b>	PA66HIRHS PA66HS
<b>Material Cable Tie</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes