

157-00034



Article Number: 157-00034

Wide Strap Cable Tie, 8mm Stud Mount, 9.7" Length, 0.5" Width, PA66HIRHSUV, Black, 300/pkg



Download drawing



Download spec sheet

Base Data

Local Order Number 157-00034

Type WSS8MM

Color Black (BK)

- Features and Benefits**
- Mount provides low insertion and high extraction forces which makes for a strong and easy installation.
 - Clamping rails increase grip on round bundles.
 - Thinner strap provides increased flexibility for improved ergonomics.
 - Tie utilizes a strong hinge between the stud mount and strap head to provide superior holding ability.

Product Description Wide Strap Heavy Duty Cable Ties features a stud mount for direct application onto an 8 mm threaded stud. The tie is 0.5" wide, and handles bundles from 0.38" - 2.3". The low profile mount design engages a minimum of 4 threads on the stud, which makes it easier to apply additional mounts onto one stud.

Short Description Wide Strap Cable Tie, 8mm Stud Mount, 9.7" Length, 0.5" Width, PA66HIRHSUV, Black, 300/pkg

Product Dimensions

Minimum Tensile Strength (Imperial) 120.0 lbs

Minimum Tensile Strength (Metric) 534 N

Length L (Imperial) 9.7 "

Length L (Metric) 246.4 mm

Fixation Method Weld Stud Fixing

Identification Plate Position none

Releasable Closure No

Tie Closure plastic pawl

Variant Inside Serrated

Width W (Imperial) 0.5 "

Width W (Metric) 12.7 mm

Bundle Diameter Min. (Imperial) 0.38 "

Bundle Diameter Min. (Metric) 9.5 mm

Bundle Diameter Max. (Imperial) 2.3 "

Bundle Diameter Max. (Metric) 57.1 mm

Stud Size (Imperial) 0.315 "

Stud Size (Metric) 8.0 mm

Logistics and Packaging

Quantity Per bag

Package Quantity (Metric) 300 Pieces

Carton Quantity 1200

Material and Specifications

Material Polyamide 6.6 high impact modified, heat and UV-resistant (PA66HIRHSUV)

Material Shortcut PA66HIRHSUV

Flammability UL94 HB

Operating Temperature -65°F to +212°F (-54°C to +100°C)

ROHS Compliant Yes