

157-00105



Article Number: 157-00105

Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 1000/pkg



Download drawing



Download spec sheet

## Base Data

<b>Local Order Number</b>	157-00105
<b>Type</b>	T50SOSB5-High-E-C-CC
<b>Color</b>	Black (BK)
<b>Features and Benefits</b>	<ul style="list-style-type: none"> <li>• Head allows for a .2" lateral adjustment on stud during installation.</li> <li>• Quick and easy installation ideal for manufacturing environment.</li> </ul>
<b>Product Description</b>	Oval Shaped Stud Mount's special design allows for a .2" (5.5mm) lateral adjustment, allowing for any misalignment of the stud or incorrect position of the tie on the cables. The "soft push" mount allows it to be installed onto a weld stud without the use of any tools.
<b>Short Description</b>	Oval Shaped Stud Mount Ties, 6.6" Long, 50lb Tensile, With Thumb Bar, PA66HS, Black, 1000/pkg

## Product Dimensions

<b>Minimum Tensile Strength (Imperial)</b>	50.0 lbs
<b>Minimum Tensile Strength (Metric)</b>	225 N
<b>Length L (Imperial)</b>	6.6 "
<b>Length L (Metric)</b>	167.0 mm
<b>Fixation Method</b>	Weld Stud Fixing
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Outside Serrated
<b>Width W (Imperial)</b>	0.2 "
<b>Width W (Metric)</b>	5.0 mm
<b>Bundle Diameter Min. (Imperial)</b>	0.04 "
<b>Bundle Diameter Min. (Metric)</b>	1.0 mm
<b>Bundle Diameter Max. (Imperial)</b>	1.4 "
<b>Bundle Diameter Max. (Metric)</b>	35.0 mm
<b>Stud Length Max. (Imperial)</b>	0.56 "
<b>Stud Length Max. (Metric)</b>	14.2 mm
<b>Stud Size (Imperial)</b>	0.2 "
<b>Stud Size (Metric)</b>	5.0 mm

## Logistics and Packaging

<b>Quantity Per</b>	bag
<b>Package Quantity (Metric)</b>	1000

## Material and Specifications

---

<b>Material</b>	Polyamide 6.6 heat stabilized (PA66HS)
<b>Material Shortcut</b>	PA66HS
<b>Flammability</b>	UL94 V2
<b>Operating Temperature</b>	-40°F to +221°F (-40°C to +105°C)
<b>ROHS Compliant</b>	Yes