

161-63203



**Article Number:** 161-63203

**Helawrap, HWPAV016, 5/8" (16mm) Dia., PA6V0, Black, 100ft/Reel**



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 161-63203

**Type** HWPAV016

**Color** Black (BK)

- Features and Benefits**
- Unique open design allows for easy branch-offs at any point along the harness.
  - Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
  - Flexible construction and design is well suited for applications that involve movement and vibration.
  - Easy to use installation tool makes assembly fast and easy.

**Product Description** The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

**Short Description** Helawrap, HWPAV016, 5/8" (16mm) Dia., PA6V0, Black, 100ft/Reel

## Product Dimensions

**Length L (Imperial)** 100.0 ft

**Length L (Metric)** 30.48 m

**Reel Length (imperial)** 100.0 ft

**Variant** Spiral Binding

**Bundle Diameter Min. (Imperial)** 0.51 "

**Bundle Diameter Min. (Metric)** 12.95 mm

**Bundle Diameter Max. (Imperial)** 0.63 "

**Bundle Diameter Max. (Metric)** 16.0 mm

**Diameter D (imperial)** 0.5 "

**Diameter D (metric)** 16.0 mm

**Nominal Diameter (Imperial)** 5/8 "

**Nominal Diameter (Metric)** 16.0 mm

**Wall Thickness WT (Imperial)** 0.03 "

**Wall Thickness WT (Metric)** 0.80 mm

**Pitch (imperial)** 0.51 "

**Pitch (metric)** 12.95 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 100.0 ft

**Package Quantity (Metric)** 30.48 m

**Carton Quantity** 30.48 m  
**Weight (Metric)** 1.79 kg  
**Weight (imperial)** 3.95 lbs

## Material and Specifications

---

**Material** Polyamide 6 V0 (PA6V0)  
**Material Shortcut** PA6V0  
**Flammability** UL94 V0  
**Halogenfree** Yes  
**Operating Temperature** -40°F to +194°F (-40°C to +90°C)  
**ROHS Compliant** Yes  
**Certification/Specification** UL-Recognized  
CEN TS 45545-2: 2009  
**UL Recognized (US)** Yes