

161-63503



Article Number: 161-63503

Helawrap, HWPAV030, 1-1/4" (30mm) Dia., PA6V0, Black, 100ft/Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 161-63503

Type HWPAV030

Color Black (BK)

- Features and Benefits**
- Unique open design allows for easy branch-offs at any point along the harness.
 - Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
 - Flexible construction and design is well suited for applications that involve movement and vibration.
 - Easy to use installation tool makes assembly fast and easy.

Product Description The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

Short Description Helawrap, HWPAV030, 1-1/4" (30mm) Dia., PA6V0, Black, 100ft/Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Variant Spiral Binding

Bundle Diameter Min. (Imperial) 1.14 "

Bundle Diameter Min. (Metric) 28.96 mm

Bundle Diameter Max. (Imperial) 1.26 "

Bundle Diameter Max. (Metric) 32.0 mm

Diameter D (imperial) 1.25 "

Diameter D (metric) 30.0 mm

Nominal Diameter (Imperial) 1-1/4 "

Nominal Diameter (Metric) 30.0 mm

Wall Thickness WT (Imperial) 0.04 "

Wall Thickness WT (Metric) 1.30 mm

Pitch (imperial) 0.94 "

Pitch (metric) 23.88 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100.0 ft

Package Quantity (Metric) 30.48 m

Carton Quantity 30.48 m
Weight (Metric) 4.46 kg
Weight (imperial) 9.83 lbs

Material and Specifications

Material Polyamide 6 V0 (PA6V0)
Material Shortcut PA6V0
Flammability UL94 V0
Halogenfree Yes
Operating Temperature -40°F to +194°F (-40°C to +90°C)
ROHS Compliant Yes
Certification/Specification CEN TS 45545-2: 2009
UL-Recognized
UL Recognized (US) Yes