

161-64417



**Article Number:** 161-64417

**Helawrap, HWPP25, Convenience Pack, 1" (25mm) Dia., PP, White, 10ft/pkg**



Download spec sheet



Download tech sheet

## Base Data

**Local Order Number** 161-64417

**Type** HWPP25

**Color** White (WH)

- Features and Benefits**
- Unique open design for easy branch-offs at any point along the harness.
  - Overwrap formation provides abrasion protection and accommodates multiple bundle configurations.
  - Flexible construction and design eliminates pinch points and minimizes bending fatigue, making it ideal for applications involving movement and vibration.
  - Split shape allows for future access without disassembly.

**Product Description** The Helawrap cable management system is the flexible routing and protection solution for industrial, datacom and electrical applications. Helawrap easily wraps around cables with a "zipper-like" motion to protect against abrasion and mechanical stress caused by movement and bending. A handy application tool is included in every package for faster installations.

**Short Description** Helawrap, HWPP25, Convenience Pack, 1" (25mm) Dia., PP, White, 10ft/pkg

## Product Dimensions

**Length L (Imperial)** 10.0 ft

**Length L (Metric)** 3.05 m

**Reel Length (imperial)** 10.0 ft

**Variant** Spiral Binding

**Bundle Diameter Min. (Imperial)** 0.91 "

**Bundle Diameter Min. (Metric)** 23.11 mm

**Bundle Diameter Max. (Imperial)** 1.06 "

**Bundle Diameter Max. (Metric)** 26.92 mm

**Diameter D (imperial)** 1.0 "

**Diameter D (metric)** 25.40 mm

**Nominal Diameter (Imperial)** 1 "

**Nominal Diameter (Metric)** 25.0 mm

**Wall Thickness WT (Imperial)** 0.04 "

**Wall Thickness WT (Metric)** 10.41 mm

**Pitch (imperial)** 0.79 "

**Pitch (metric)** 20.07 mm

## Logistics and Packaging

**Quantity Per** bag

**Package Quantity** 10.0 ft

**Package Quantity (Metric)** 3.05 m  
**Carton Quantity** 3.05 m  
**Weight (imperial)** 0.65 lbs  
**Weight (Metric)** .29 kg

## Material and Specifications

---

**Material** Polypropylene (PP)  
**Material Shortcut** PP  
**Flammability** UL94 HB  
**Halogenfree** Yes  
**Operating Temperature** -76°F to +230°F (-60°C to +110°C)  
**ROHS Compliant** Yes