# HellermannTyton


## 166-90128



Article Number: 166-90128

HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.38" Dia., PA66, Black, 10/pkg

RoHS





#### **Base Data**

Local Order Number 166-90128

Type PSR038-90-0500

Color Black (BK)

- Features and Benefits External NPT thread provides a secure connection.
  - Twist-on installation makes future access fast and easy.
  - · Internal spigot design helps ease threading of fitting onto conduit.
  - All-around "teeth" attach firmly to conduit and deliver a high extraction force.
  - Durable nylon material has high resistance to salts, oils, weak acids and solvents.
  - IP65 rating for protection against wind, dirt and low pressure jets of water from all directions.

Product Description Compression fittings feature a twist-on design for easy installation and future access. Constructed of a very durable nylon material with a high resistance to salts, oils, weak acids and solvents. Fits HelaGuard non-metallic conduits

and tubing.

Short Description HelaGuard Non Metallic IP65 Compression Fitting, 90 Degree Elbow, NPT Thread, 0.38" Dia., PA66, Black, 10/pkg

### **Product Dimensions**

Length L (Imperial) 2.01 "

Length L (Metric) 51 mm

Bore Diameter (Imperial) 0.41 "

Bore Diameter (Metric) 10.5 mm

Clearance Hole Diameter (Imperial) 0.827 "

Clearance Hole Diameter (Metric) 21 mm

Thread Length (Imperial) 0.51 "

Trade Size 3/8"

Outside Diameter D (imperial) 1.10 "

Outside Diameter D (metric) 28 mm

Nominal Diameter (Imperial) 3/8 "

Nominal Diameter (Metric) 16 mm

Thread Length (metric) 13 mm

## **Logistics and Packaging**

Quantity Per bag

Package Quantity 10

Package Quantity (Metric) 10 Pieces

## **Material and Specifications**

Material Polyamide 6.6 (PA66)

Material Shortcut PA66

Flammability UL94 V2

**Operating Temperature** -40°F to +248°F (-40°C to +120°C)

ROHS Compliant Yes

UL Listed (US and Canada) No

UL Listed (US) No

UL Recognized (US) Yes

UL Recognized (US and Canada) Yes