HellermannTyton

166-90272

166-90272	
He	ticle Number: 166-90272 IaGuard Non Metallic Conduit, Std. Weight, 0.75" Dia., Nylon PA6 Slit, Black, 100.0 ft/Std. Reel
Download spec sheet	
Base Data	166-90272
	HG-SWSL0750
	Black (BK)
	 Material is easy to use and cut; reduces installation time and labor costs. Flexible, abrasion resistant and durable for a variety of applications. Good impact strength; recovers quickly if crushed. UV resistant; suitable for use in outdoor applications. Offered in fine or course corrugated pitch. Offered with or without slit; slit options offer easy access during installation and maintenance.
Product Description	A standard weight corrugated conduit made of PA6 nylon that offers flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection against water, wind and dirt.
Short Description	HelaGuard Non Metallic Conduit, Std. Weight, 0.75" Dia., Nylon PA6 Slit, Black, 100.0 ft/Std. Reel
Product Dimensions	
Length L (Imperial)	100.0 ft
Length L (Metric)	30.5 m
Inner Diameter D (Imperial)	0.90 "
Inner Diameter D (metric)	22.8 mm
Euro (NW) Size	23 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	100 ft
Package Quantity (Metric)	30.5 m

Outside Diameter D (imperial)1.13 "Outside Diameter D (metric)28.5 mmNominal Diameter (Imperial)3/4 "Nominal Diameter (Metric)28 mmInside Bend Radius (Imperial)1.97 "Inside Bend Radius (Metric)50 mm

Pitch TypeF (Fine)Trade Size3/4 "

Material and Specifications

Polyamide 6 (PA6)
PA6
UL94 V2
Yes
-40°F to +248°F (-40°C to +120°C)
Yes
No
No
Yes
Yes

© HellermannTyton 2015