

166-90274



Article Number: 166-90274

HelaGuard Non Metallic Conduit, Std. Weight, 1.25" Dia., Nylon PA6 Slit, Black, 50.0 ft/Std. Reel



Download spec sheet



Download tech sheet

Base Data

Local Order Number 166-90274

Type HG-SWSL1250

Color Black (BK)

- Features and Benefits**
- Material is easy to use and cut; reduces installation time and labor costs.
 - Flexible, abrasion resistant and durable for a variety of applications.
 - Good impact strength; recovers quickly if crushed.
 - UV resistant; suitable for use in outdoor applications.
 - Offered in fine or coarse corrugated pitch.
 - Offered with or without slit; slit options offer easy access during installation and maintenance.

Product Description A standard weight corrugated conduit made of PA6 nylon that offers flexible abrasion protection for wire and cable bundles. Easy to cut and use, the material is highly resistant to solvents and oils. Combine with HelaGuard non-metallic fittings for IP66 rating or greater protection against water, wind and dirt.

Short Description HelaGuard Non Metallic Conduit, Std. Weight, 1.25" Dia., Nylon PA6 Slit, Black, 50.0 ft/Std. Reel

Product Dimensions

Length L (Imperial)	50.0 ft
Length L (Metric)	15.2 m
Inner Diameter D (Imperial)	1.40 "
Inner Diameter D (metric)	35.5 mm
Euro (NW) Size	36 mm
Pitch Type	C (Coarse)
Trade Size	1-1/4 "
Outside Diameter D (imperial)	1.68 "
Outside Diameter D (metric)	42.5 mm
Nominal Diameter (Imperial)	1-1/4 "
Nominal Diameter (Metric)	42 mm
Inside Bend Radius (Imperial)	2.76 "
Inside Bend Radius (Metric)	70 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	50 ft
Package Quantity (Metric)	15.2 m

Material and Specifications

Material	Polyamide 6 (PA6)
Material Shortcut	PA6
Flammability	UL94 V2
Halogenfree	Yes
Operating Temperature	-40°F to +248°F (-40°C to +120°C)
ROHS Compliant	Yes
UL Listed (US)	Yes
UL Listed (US and Canada)	Yes
UL Recognized (US)	No
UL Recognized (US and Canada)	No