

169-60022



Article Number: 169-60022

Convoluted Tubing, Slit, 1/4" Dia., PA6, Black w/Gray Stripe, 100ft/Box



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 169-60022

**Type** CTN140

**Color** Black with Gray Stripe (BKSTGY)

**Features and Benefits**

- Durable tubing provides protection of wire harness from friction, vibration, fraying and puncture
- Tubing protects cables and wires against automotive fluids, vibration wear
- Weather resistant material provides protection against water, snow, ice, and the effects of heat, cold, and sunlight

**Product Description** HellermannTyton's Convoluted Tubing, also known as Split Loom Tubing, provides an efficient method of routing and protecting wire harness assemblies, while reducing the chance of installation damage. With a split down the side where you can insert your wire harness, you can just easily install Convoluted Tubing without removal of the entire assembly. It can also serve to protect valuable hoses and cables. Convoluted tubing offer's excellent protection against vibration wear, water, snow, ice and the effects of heat, cold and sunlight on cables and wires.

**Short Description** Convoluted Tubing, Slit, 1/4" Dia., PA6, Black w/Gray Stripe, 100ft/Box

## Product Dimensions

<b>Length L (Imperial)</b>	100.0 ft
<b>Length L (Metric)</b>	30.5 m
<b>Inner Diameter D (Imperial)</b>	0.276 "
<b>Inner Diameter D (metric)</b>	7.01 mm
<b>Diameter D (imperial)</b>	0.398 "
<b>Diameter D (metric)</b>	10.11 mm
<b>Diameter D2 (imperial)</b>	0.276 "
<b>Diameter D2 (metric)</b>	7.01 mm
<b>Outside Diameter D (imperial)</b>	0.398 "
<b>Outside Diameter D (metric)</b>	10.11 mm
<b>Nominal Diameter (Imperial)</b>	1/4 "
<b>Nominal Diameter (Metric)</b>	6.35 mm
<b>Wall Thickness WT (Imperial)</b>	0.004 "
<b>Wall Thickness WT (Metric)</b>	0.102 mm

## Logistics and Packaging

<b>Quantity Per</b>	box
<b>Package Quantity</b>	100.0 ft
<b>Package Quantity (Metric)</b>	30.5 m
<b>Carton Quantity</b>	3

## Material and Specifications

---

<b>Material</b>	Polyamide 6 (PA6)
<b>Material Shortcut</b>	PA6
<b>Flammability</b>	UL94 HB
<b>Operating Temperature</b>	-40°F to +300°F (-40°C to +149°C)
<b>ROHS Compliant</b>	Yes