

170-03012



Article Number: 170-03012

Fray Resistant Expandable Braided Sleeveing, 0.5" Dia., PET, Black, 100.0 ft/Standard Reel



Download drawing



Download spec sheet

## Base Data

Local Order Number 170-03012

Type BSPSC120

Color Black (BK)

- Features and Benefits**
- Cuts with scissors without fraying ends enables field installations without need for hot knife.
  - Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.
  - Expands to 150% of easy installation and reduced assembly time requirements.

**Product Description** A versatile and economical general purpose braided sleeveing that resists fraying when cut with ordinary scissors.

**Short Description** Fray Resistant Expandable Braided Sleeveing, 0.5" Dia., PET, Black, 100.0 ft/Standard Reel

## Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Min. (Imperial) 0.25 "

Bundle Diameter Min. (Metric) 6.4 mm

Bundle Diameter Max. (Imperial) 0.75 "

Bundle Diameter Max. (Metric) 19.1 mm

Nominal Diameter (Imperial) 1/2 "

Nominal Diameter (Metric) 12.7 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Package Quantity (Metric) 100.0 ft

Weight (Metric) 0.37 kg

Weight (imperial) 0.82 lbs

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes

---

© HellemannTyton 2015