

170-03014



Article Number: 170-03014

Fray Resistant Expandable Braided Sleeving, 1.0" Dia., PET, Black, 50.0 ft/Standard Reel



Download drawing



Download spec sheet

Base Data

Local Order Number 170-03014

Type BSPSC100

Color Black (BK)

- Features and Benefits**
- Cuts with scissors without fraying ends enables field installations without need for hot knife.
 - Material construction offers excellent abrasion and cut-through protection as well as inertness to common chemicals and fungus.
 - Expands to 150% of easy installation and reduced assembly time requirements.

Product Description A versatile and economical general purpose braided sleeving that resists fraying when cut with ordinary scissors.

Short Description Fray Resistant Expandable Braided Sleeving, 1.0" Dia., PET, Black, 50.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Min. (Imperial) 0.75 "

Bundle Diameter Min. (Metric) 19.1 mm

Bundle Diameter Max. (Imperial) 1.19 "

Bundle Diameter Max. (Metric) 30.2 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 50 ft

Package Quantity (Metric) 50.0 ft

Weight (imperial) 0.62 lbs

Weight (Metric) 0.28 kg

Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL94 V0

Operating Temperature -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes

© HellemannTyton 2015