

170-03018



Article Number: 170-03018

Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.75" Dia., Black, 75.0 ft/Standard Reel



Download drawing



Download spec sheet

## Base Data

Local Order Number 170-03018

Type BSSCFR340

Color Black (BK)

- Features and Benefits**
- Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.
  - Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.
  - Cuts with ordinary scissors without fraying ends.

**Product Description** Treated polyester yarns that can be cut with sharp scissors and provides flame retardant properties. Well suited for situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy identification.

**Short Description** Fray Resistant Flame Retardant Expandable Braided Sleeveing, 0.75" Dia., Black, 75.0 ft/Standard Reel

## Product Dimensions

Length L (Imperial) 75.0 ft

Length L (Metric) 22.9 m

Reel Length (imperial) 75.0 ft

Bundle Diameter Min. (Imperial) 0.625 "

Bundle Diameter Min. (Metric) 15.9 mm

Bundle Diameter Max. (Imperial) 1.0 "

Bundle Diameter Max. (Metric) 25.4 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

## Logistics and Packaging

Quantity Per reel

Package Quantity 75 ft

Weight (Metric) 0.38 kg

Weight (imperial) 0.83 lbs

## Material and Specifications

Material Polyester (PET)

Material Shortcut PET

Flammability UL VW-1  
Mil-202

Operating Temperature -94°F to +257°F (-70°C to +125°C)

**ROHS Compliant** Yes

**UL Recognized (US and Canada)** Yes