# HellermannTyton

### 170-03019



Article Number: 170-03019

Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 50.0 ft/Standard Reel

RoHS





#### **Base Data**

Local Order Number 170-03019

Type BSSCFR100

Color Black (BK)

Features and Benefits • Increased braid density coverage provides higher level of abrasion resistance without losing flexibility.

• Treated yarns extinguish quickly and reduces potential flame spread to surrounding components.

· Cuts with ordinary scissors without fraying ends.

Product Description Treated polyester yams that can be cut with sharp scissors and provides flame retardant properties. Well suited for

situations where access to a hot knife is either impractical or impossible. Contains white tracer thread for easy

identification.

Short Description Fray Resistant Flame Retardant Expandable Braided Sleeving, 1.0" Dia., Black, 50.0 ft/Standard Reel

#### **Product Dimensions**

Length L (Imperial) 50.0 ft

Length L (Metric) 15.2 m

Reel Length (imperial) 50.0 ft

Bundle Diameter Min. (Imperial) 0.75 "

Bundle Diameter Min. (Metric) 19.1 mm

Bundle Diameter Max. (Imperial) 1.188 "

Bundle Diameter Max. (Metric) 30.2 mm

Nominal Diameter (Imperial) 1 "

Nominal Diameter (Metric) 25.4 mm

## **Logistics and Packaging**

Quantity Per reel

Package Quantity 50 ft

Weight (Metric) 0.28 kg

Weight (imperial) 0.62 lbs

## **Material and Specifications**

Material Polyester (PET)

Material Shortcut PET

Flammability Mil-202

UL VW-1

**Operating Temperature** -94°F to +257°F (-70°C to +125°C)

ROHS Compliant Yes

UL Recognized (US and Canada) Yes

© HellermannTyton 2015