

170-03051

Article Number: 170-03051

Resin Coated Fiberglass Sleeving, 0.5" Dia., Black, 200.0 ft/Bulk Reel



Download drawing



Download spec sheet

## Base Data

**Local Order Number** 170-03051

**Type** BSHTFG120B

**Color** Black (BK)

- Features and Benefits**
- An extremely tough sleeving material which provides thermal protection up to 1,200°F.
  - Sturdy construction maintains its tight structure under extreme shaking, scraping, pressure and varying temperature conditions.
  - Cuts easily with ordinary scissors for easy application.
  - UL VW-1 flammability rating for use in conditions requiring a very high degree of flame resistance.

**Product Description** An extremely high-temperature resistant sleeving designed to protect wires and cables subjected to continuous temperature variations, vibration, abrasion, and mechanical stress.

**Short Description** Resin Coated Fiberglass Sleeving, 0.5" Dia., Black, 200.0 ft/Bulk Reel

## Product Dimensions

**Length L (Imperial)** 200.0 ft

**Length L (Metric)** 61.0 m

**Reel Length (imperial)** 200.0 ft

**Bundle Diameter Max. (Imperial)** 0.75 "

**Bundle Diameter Max. (Metric)** 19.1 mm

**Nominal Diameter (Imperial)** 1/2 "

**Nominal Diameter (Metric)** 12.7 mm

## Logistics and Packaging

**Quantity Per** reel

**Package Quantity** 200 ft

**Package Quantity (Metric)** 200.0 ft

**Weight (imperial)** 9.6 lbs

**Weight (Metric)** 4.35 kg

## Material and Specifications

**Material** Glass Fiber (GF)

**Operating Temperature** -94°F to +1202°F (-70°C to +650°C)

**ROHS Compliant** Yes

**UL Recognized (US)** Yes

