

170-03055

Article Number: 170-03055

Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver, 250.0 ft/Bulk Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03055

Type BSHTTST34SRB

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
 - Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeving Tube, 0.75" Dia., Silver, 250.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial) 250.0 ft

Length L (Metric) 76.2 m

Reel Length (imperial) 250.0 ft

Bundle Diameter Max. (Imperial) 0.687 "

Bundle Diameter Max. (Metric) 17.4 mm

Nominal Diameter (Imperial) 3/4 "

Nominal Diameter (Metric) 19.1 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 250 ft

Package Quantity (Metric) 1 Reel

Weight (imperial) 8.625 lbs

Weight (Metric) 3.91 kg

Material and Specifications

Material Aluminium (AL)
Glass Fiber (GF)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes

