HellermannTyton

170-03056

170-03050			
Art	ticle Number: 170-03056		
Alu	uminum Laminated Fiberglass Sleeving Tube, 1.0" Dia., Silver, 250.0 ft/Bulk Reel		
Notes VI	¢ RoHS		
Download drawing	spec sheet Download tech sheet		
Base Data			
Local Order Number	170-03056		
Туре	BSHTTST10SRB		
Color	Silver (SR)		
Features and Benefits	Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.		
	Cuts with ordinary scissors for fast, easy application.		
Product Description	A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.		
	Aluminum Laminated Fiberglass Sleeving Tube, 1.0" Dia., Silver, 250.0 ft/Bulk Reel		

Product Dimensions

Length L (Imperial)	250.0 ft
Length L (Metric)	76.2 m
Reel Length (imperial)	250.0 ft
Bundle Diameter Max. (Imperial)	0.937 "
Bundle Diameter Max. (Metric)	23.8 mm
Nominal Diameter (Imperial)	1 "
Nominal Diameter (Metric)	25.4 mm

Logistics and Packaging

Quantity Per	reel
Package Quantity	250 ft
Package Quantity (Metric)	1
Weight (imperial)	11.25 lbs
Weight (Metric)	5.08 kg

Material and Specifications

Material	Aluminium (AL) Glass Fiber (GF)
Flammability	non flammable
Operating Temperature	-76°F to +491°F (-60°C to +255°C)
ROHS Compliant	Yes

© HellermannTyton 2015