HellermannTyton

170-03057



Article Number: 170-03057

Aluminum Laminated Fiberglass Sleeving, 1.75" Dia., Silver, 100.0 ft/Bulk Reel

RoHS







Base Data

Local Order Number 170-03057

Type BSHTTST134SRB

Color Silver (SR)

- Features and Benefits A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature

environments.

• Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single

solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeving, 1.75" Dia., Silver, 100.0 ft/Bulk Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Max. (Imperial) 1.687 "

Bundle Diameter Max. (Metric) 42.8 mm

Nominal Diameter (Imperial) 1-3/4 "

Nominal Diameter (Metric) 44.5 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Package Quantity (Metric) 1 Reel

Weight (imperial) 7.40 lbs

Weight (Metric) 3.36 kg

Material and Specifications

Material Glass Fiber (GF)

Aluminium (AL)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes

