

170-03062



Article Number: 170-03062

Aluminum Laminated Fiberglass Sleeve Tube, 0.5" Dia., Silver, 100.0 ft/Standard Reel



Download drawing



Download spec sheet



Download tech sheet

Base Data

Local Order Number 170-03062

Type BSHTTST12SR

Color Silver (SR)

- Features and Benefits**
- A layer of aluminum provides protection from chemicals, scraping, cuts and abrasion.
 - Additional layer also provides insulation barrier for vulnerable wires and cables within high temperature environments.
 - Cuts with ordinary scissors for fast, easy application.

Product Description A tubular shaped sleeving product that combines the protection of bonded aluminum and fiberglass into a single solution that is able to deflect radiant heat away from sensitive components inside the tube.

Short Description Aluminum Laminated Fiberglass Sleeve Tube, 0.5" Dia., Silver, 100.0 ft/Standard Reel

Product Dimensions

Length L (Imperial) 100.0 ft

Length L (Metric) 30.48 m

Reel Length (imperial) 100.0 ft

Bundle Diameter Max. (Imperial) 0.437 "

Bundle Diameter Max. (Metric) 11.1 mm

Nominal Diameter (Imperial) 1/2 "

Nominal Diameter (Metric) 12.7 mm

Logistics and Packaging

Quantity Per reel

Package Quantity 100 ft

Package Quantity (Metric) 1 Reel

Weight (Metric) 1.16 kg

Weight (imperial) 2.55 lbs

Material and Specifications

Material Glass Fiber (GF)
Aluminium (AL)

Flammability non flammable

Operating Temperature -76°F to +491°F (-60°C to +255°C)

ROHS Compliant Yes

